



## **MPOS 150** **15" Touch Screen Pc POS**

"All in one" PcPOS system  
Sturdy and reliable  
15" monitor with resistive ELO touch  
Adjustable monitor slope (90°)  
Industrial electronics  
Embedded customer display (optional)



**MPOS150** is an "all in one" PC POS specifically designed and created to answer to the needs of Retail and Hospitality markets. Elegant and sturdy, **MPOS150** is equipped with an ELO touch screen (5 wires resistive) with 15" backlit LCD monitor (1024x768 resolution); monitor slope angle 90°.

### **Main features and capabilities:**

- Celeron Mobile 550 processor
- 1GB RAM DDRII 667 MHz
- Hard disk 80 GB SATA
- 1 Ethernet board 10/100
- 4 serial interfaces (internal COM3)
- 4 USB interfaces (2 front and 2 back)
- 1 parallel interface
- 1 PS/2
- 1 external VGA port
- MIC-in, speaker-out (frontal entrance)
- Dedicated connection for the cash drawer
- 15" LCD monitor 1024x768
- 5 wires resistive touch screen
- Power supply 110- 240W
- Size (printer excluded):  
379mm (L)x312mm (D)x358mm (H)

**MPOS150** offers a wide versatility thanks to his optional peripherals, such as the magnetic card reader, the **VFD** customer display and the 10.4" **LCD** customer monitor.



	<b>MPOS 150</b>
<b>Processor</b>	CPU Intel Celeron M 550 2 GHz
<b>Memory</b>	1 GB (max 2 GB) DDRII 667 MHz
<b>Compact flash</b>	1 x Slot Tipo II (optional)
<b>Hard disk</b>	2.5", 80 GB SATA HDD
<b>Display</b>	15" LCD display with touch screen
<b>Resolution</b>	1024 x 768
<b>Brightness</b>	250cd/m2
<b>Touch screen</b>	ELO 5- wire resistive type
<b>Back panel I/O connectors</b>	4 Serial Ports, COM 1,2 & 4 with +5V/12V power output, COM 3 is internal type reserved for touchscreen, optional COM 5
	1 parallel Port: supports SPP/EPP/ECP
	4 USB 2.0 powered (2 front & 2 rear access)
	1 PS/2 Mouse + Keyboard Interface
	1 Ethernet 10/100Mb interface (RJ45)
	1 Cash Drawer RJ-11 with 12V power output
	1 VGA port
<b>Audio</b>	MIC-in, Speaker-out (front access) + 2x speakers 1 slot Mini PCI
<b>Power supply</b>	Internal 120W, ATX Active PFC; 110 ÷ 240W
<b>Dimensions (WxDxH)</b>	379x312x358mm
<b>Optional Accessory</b>	VFD customer display
	Magnetic card reader
	Dallas key reader
	2nd display monitor 10.4"
	Slim CD ROM module